Active Foam CP 940

Slightly alkaline active foam for a stable foam in self-service wash systems. The VDA-compliant active foam with a pleasant lemon scent is gentle on the paintwork thanks to its good rinsing properties.

pH value 8
in concentrate



Made in Germany

NTA-free

Properties

- Foam-intensive brush shampoo for car washing
- Removes oil, grease and mineral contamination
- Creates a voluminous, bright and attractive foam
- Helps the brushes to slide and therefore protects the vehicle surface
- Significantly reduces the resoiling of the brushes
- Is wax-compatible to prevent streaking on the surface of the paintwork
- VDA-compliant
- Quick oil and water separation in the oil separator (easily separable = asf)
- Tensides biodegradable in accordance with OECD
- NTA free

Application areas

Car dealership and garage	Vehicle cleaning
Haulage contractors, bus operators	Commercial vehicle cleaning
Self-service washing stations	Cars, commercial vehicles, bicycles
Vehicle wash system	Cars

Usage options

- High-pressure cleaners
- Car washes
- Self-service washing stations
- High-pressure cleaner with foam nozzle

Technical data

Container sizes	Packaging unit	Part number
20 l	1 Piece(s)	6.295-519.0
200 l	1 Piece(s)	6.295-520.0

Active Foam CP 940, 0.011-365.0, 2026-08-28

We would be happy to advise you: Kärcher (U.K.) Ltd. * Kärcher House * Brookhill Way * Banbury * Oxon OX16 3ED

Application

High-pressure cleaners
- Apply primary mixture with fresh water.
- Set the dosage and temperature on the device
- 1-40°C processing temperature.
- Wet object completely with the product.
- Allow to soak.
- Contact time 1-5 minutes, depending on the degree of soiling.
- Rinse surface well with clear water.

Car washes
- Insert the product into the system.
- Adjust dosage on the device.
- Start washing programme.

Self-service washing station
- Apply primary mixture with fresh water.
- Set the dosage and temperature on the device
- 1-40°C processing temperature.
- Wet object completely with the product.
- Allow to soak.
- Contact time 1-5 minutes, depending on the degree of soiling.
- Rinse surface well with clear water.

Instructions for use

- Do not let the cleaning solution dry out.
- Do not apply to alkali-sensitive surfaces.
- Store away from frost.

Warnings and safety recommendations according to EC Directives

- Danger
- H315 Causes skin irritation
- H318 Causes serious eye damage
- P264 Wash thoroughly after handling.
- P280a Wear protective gloves / eye protection / face protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.

Further information

- VDA certification
- Material Safety Data Sheet (MSDS)

Dosage and yield

Contents	Cleaning method	Dosage	Soiling	Productivity
1000 ml	High-pressure cleaners	1.3 – 2 %	strong	100 Car
1000 ml	Vehicle wash system	1.3 – 2 %	medium	100 Car
1000 ml	Self-service washing stations	0.2 %	strong	70 Car
1000 ml	High-pressure cleaner with foam nozzle	1.3 – 2 %	medium	100 Car

Active Foam CP 940, 0.011-365.0, 2026-08-28