



Blasting Abrasive, coarse

Spray agent with a granulation of 0.25–1.4 mm. Highly effective on steel, granite, aerated and exposed aggregated concrete. Also ideal for removing rust, paint and graffiti.



Properties

- For use with Kärcher blasting systems and guns
- Spray agent made from granulated melting chamber slag (aluminium silicate base)
- Granulation 0.25-1.4mm
- Hardness on the Mohs scale: 6-7
- For removing coarse dirt on surfaces such as steel, granite, clinker, porphyry, concrete, aerated and exposed aggregated concrete

Usage options

- High-pressure cleaner with jet system and jet gun

Application areas

Agriculture	Derusting
Building Industry	Cleaning concrete and formwork material
Building cleaning	Façade cleaning
Municipal	Derusting, graffiti removal

Technical data

Container sizes	Packaging unit	Part number
25 kg	1 Piece(s)	6.295-565.0

Application

High-pressure cleaner with jet system and jet gun

- High-pressure cleaner equipped with jet system and gun.
- Insert spray agent intake into spray agent.
- Adjust volume regulation as required.
- Spray object.

Instructions for use

- Test on an inconspicuous part for material compatibility.
- Store in a dry place.
- Removing spray agent deposits with the air or water stream.

Further information

- Material Safety Data Sheet (MSDS)

Dosage and yield

Contents	Cleaning method	Dosage	Soiling	Productivity
25 kg	High-pressure cleaner with jet system and jet gun	tailored to individual requirements	strong	dosage-dependent