WaterPro Flocculating Agent RM 847

For the effective treatment of contaminated water from car and engine washes. Forms large and easily filtered flakes.

pH value 4
in concentrate



Made in Germany

Properties

- Effective reaction separating agent on a polymer base for emulsion separating systems (ASA, HDR 555, HDR 777)
- Suitable for reuse of washing water on high-pressure cleaners.
- Approx. 75% of the detergent substances remain in the recycled water. As a result, a lower re-dosage of cleaning agent is possible.
- Extremely economical
- Specially adapted to Kärcher systems
- NTA free

Application areas

Car dealership and garage	Water recycling
Metalworking industry	Water recycling
Industry	Water recycling
Haulage contractors, bus operators	Water recycling

Usage options

- Water treatment systems

Technical data

Container sizes	Packaging unit	Part number
1 l	2 Piece(s)	6.295-630.0

We would be happy to advise you: Kärcher (U.K.) Ltd. * Kärcher House * Brookhill Way * Banbury * Oxon OX16 3ED

Application

Water treatment systems

- Fixed dosage is set by the service technician when installing the system.
- The set dosing amount should be observed.
- Apply primary mixture with fresh water.
- Check content of the treatment chemicals regularly.

Instructions for use

- Do not mix with other cleaning agents/chemicals.
- Use only from the original container.

Warnings and safety recommendations according to EC Directives

- H411 Toxic to aquatic life with long lasting effects
- P273 Avoid release to the environment.
- P391 Collect spillage.
- P501a Dispose of contents/container in accordance with local/regional/national/international regulations.

Further information

- Material Safety Data Sheet (MSDS)

Dosage and yield

Contents	Cleaning method	Primary mixture	Dosage	Soiling	Productivity
1000 ml	Water treatment systems	1+9	0.07 %	Mild everyday soiling (maintenance cleaning).	14000 l

WaterPro Flocculating Agent RM 847, 0.011-856.0, 2026-11-13