# AF 20

Fast air purification in rooms of 20 m² [1] to 40 m²: the compact AF 20 air purifier with H13 filtration and activated carbon reliably removes pathogens, fine dust, allergens and odours.




LASER SENSOR

ALLERGY-FRIENDLY

**Order no.** **1.024-823.0**

- Ideally suited for rooms of 20 to 40 m², max. air flow rate 220 m³/h
- Laser sensors, automatic mode, display, HEPA and activated carbon filtration

| Technical data | | |
|---|---|---|
| EAN code | | 4066529021403 |
| Number of current phases | Ph | 1 |
| Voltage | V | 100 – 240 |
| Frequency | Hz | 50 – 60 |
| Power rating | W | 24 |
| Suitable room size | m² | up to 40 |
| Air flow rate | m³/h | up to 220 |
| Filter efficiency according to particle size | | 0.3 µm >= 99.95 % |
| Power settings | | 3 |
| Colour | | white |
| Weight without accessories | kg | 3 |
| Weight incl. packaging | kg | 3.8 |
| Dimensions (L × W × H) | mm | 220 × 220 × 346 |

| Equipment |
|---|
| Dual filter system |
| Filter change indicator |
| Air quality display |
| Operation of the device with touch function |
| Automatic mode |
| Night mode |
| Locking function |
| Timer program |

[1] Recommended room size based on a ceiling height of 3 m and air exchange three times an hour for operation at the highest power level.

AF 20, 1.024-823.0, 2026-11-13






### High Protect 13 Filter

- HEPA filter for the removal of pathogens and aerosols.
- For bonding odours and chemical vapours.



### Dual air inlet system

- Thanks to the air intake on both sides, a high air flow rate is guaranteed.



### Display

- Indication of the air quality in µg/m³ as well as the filter and device status.

AF 20, 1.024-823.0, 2026-11-13

# EQUIPMENT FOR AF 20
# 1.024-823.0




| | | Order no. | Description | |
|---|---|---|---|---|
| **AIR TREATMENT** | | | | |
| Filter set AF 20 | 1 | 2.863-056.0 | Replacement filter kit for the AF 20 air purifier with H13 filter material and active carbon. | ■ |

■ Included in delivery.