

HD 8/23 G CLASSIC

Self-sufficient, mobile, powerful: HD 8/23 G Classic cold water high-pressure cleaner with robust crankshaft pump and petrol engine. For demanding applications in construction and municipalities.



Order no. 1.187-012.0

- Independent high-pressure cleaning irrespective of external power sources
- Robust crankshaft pump with ceramic pistons
- Compact, light and extremely mobile

Technical data

EAN code		4054278731827
Flow Rate	l/h	800
Operating pressure	bar / MPa	230 / 23
Max. Pressure	bar / MPa	280 / 28
Water inlet		3/4"
Drive type		Petrol
Motor type		G300FA
Number of users at one time		1
Mobility		High
Colour		anthracite
Weight (with accessories)	kg	50.9
Weight incl. packaging	kg	59
Dimensions (L × W × H)	mm	878 × 538 × 702

Scope of supply

Spray gun: Standard
High-pressure hose length: 10 m
Power nozzle
Water filter

Equipment

Cage frame
Crankshaft pump with ceramic pistons




Independence

- Allows independence of external power sources.
- Complies with the requirements of exhaust emissions standard EU STAGE V.
- Convenient manual pull start.



Outstanding mobility

- Puncture-proof wheels guarantee permanently high mobility.
- The compact and slim machine is also very easy to manoeuvre in confined areas.
- For good mobility, easy transport and space-saving storage – fits in a standard car.




Durable and sturdy

- A robust tubular steel frame reliably protects the machine against damage.
- Proven safety technology such as thermo and safety valve and water filter.
- Crankshaft pump with ceramic pistons.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0



	Order no.	Description	
TRIGGER GUNS			
Trigger guns			
Pistol	1 9.751-376.0		■
EASY!Force Advanced	2 4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	□
EASY!Force conversion kit 2 - from machine	3 4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	□
SPRAY LANCES			
Spray lance			
Spray lance 850 mm	4 9.751-146.0	Galvanised spray lance with manual screw fitting for high-pressure cleaners in the Classic range from Kärcher. Not rotatable. Length: 850 mm.	■
Jet pipe TR 1050mm with package	5 4.760-855.0	High-pressure spray lance with M 22 screw connections from the Classic series from Kärcher. Also suitable for hot water high-pressure cleaners.	□
Jet pipe Classic M 840mm	6 4.760-895.0		□
600 mm spray lance	7 9.751-140.0	600 mm long, zinc coated spray lance with hand screw connection. Not rotatable.	□
250 mm lance, non-rotatable	8 4.760-667.0	250 mm stainless steel lance. With manual coupling. Non-rotatable.	□
Rotating spray lances			
Spray lance, 600 mm, rotatable	9 4.760-664.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Spray lance, 840 mm, rotatable	10 4.760-663.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Spray lance, 1050 mm, rotatable	11 4.760-660.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Spray lance, 1550 mm, rotatable	12 4.760-661.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Spray lance, 2050 mm, rotatable	13 4.760-662.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Angular spray lance			
Spray lance for toilets and rain gutters	14 4.760-073.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0



		Order no.	Description	
SPRAY LANCES				
Flexible spray lance				
High pressure articulated joint	15	4.481-039.0	High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.	<input type="checkbox"/>
Flexible lance, 1050 mm	16	6.394-654.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	<input type="checkbox"/>
Undercarriage spray lance				
Underbody lance	17	4.760-245.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	<input type="checkbox"/>
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power nozzle 25°, 038	18	2.883-805.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	<input checked="" type="checkbox"/>
Power nozzle spray angle 15°				
Power nozzle 15°, 040	19	2.883-388.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	<input type="checkbox"/>
Power nozzle spray angle 40°				
Power Nozzle 40°, 040	20	2.884-522.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	<input type="checkbox"/>
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, ID 8, 315 bar, M22 × 1.5	21	9.751-420.0	Up to 155 °C heat-resistant high-pressure hose (DN 8) with 10 m length. Perfect for all high-pressure cleaners in the Classic range from Kärcher.	<input checked="" type="checkbox"/>
High-pressure hose, 10 m, ID 8, 315 bar, 2 × M22 × 1.5	22	6.391-342.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	<input type="checkbox"/>
High-pressure hose, 15 m, ID 8, 315 bar, 2 × M22 × 1.5	23	6.390-010.0	With screw connections on both sides, M 22 × 1.5 with bend protection.	<input type="checkbox"/>
High-pressure hose, 20 m, ID 8, 315 bar, 2 × M22 × 1.5	24	6.390-031.0	Screw connections at both ends, M 22 × 1.5, with kink protection.	<input type="checkbox"/>
High-pressure hose, 30 m, ID 8, 315 bar, 2 × M22 × 1.5	25	6.390-293.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	<input type="checkbox"/>
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × M22 × 1.5	26	6.390-178.0	1.5 m high-pressure hose (DN 8, M 22 × 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 × 1.5).	<input type="checkbox"/>
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	27	6.388-083.0	10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 × 1.5, with kink protection.	<input type="checkbox"/>
	28	6.391-354.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0




29



25, 27, 30-31



32



33



34



35



38-39, 41, 43



40, 42, 44

	Order no.	Description	
HIGH-PRESSURE HOSES			
Longlife 400 with unions on both sides			
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × M22 × 1.5	29	6.389-709.0	With rotary coupling, 2 × M 22 × 1.5 <input type="checkbox"/>
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × M22 × 1.5	30	6.390-027.0	with rotary coupling, 2 × M 22 × 1.5 <input type="checkbox"/>
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × M22 × 1.5	31	6.390-294.0	With rotary coupling, 2 × M 22 × 1.5 <input type="checkbox"/>
ROTARY NOZZLES (DIRT BLASTERS)			
Dirt blaster, large			
Dirt blaster, 040	32	4.763-252.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. <input type="checkbox"/>
ECO!BOOSTER			
Eco!Booster MAX TR 040	33	2.113-095.0	Maximum efficiency and versatility in professional cleaning. The eco!Booster MAX offers more than double the area performance and ergonomic handling. <input type="checkbox"/>
QUICK CONNECT			
Quick coupling	34	6.401-458.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread. <input type="checkbox"/>
Plug nipple	35	6.401-459.0	Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 × 1.5 external thread. <input type="checkbox"/>
DRUM AND TANK CLEANING			
Add-on kit mud sucker	36	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps. <input type="checkbox"/>
SEALS FOR TRAPEZOIDAL THREAD			
Spare part set seals TR	37	2.880-001.0	<input type="checkbox"/>
PIPE CLEANING			
Pipe cleaning hose, ID 6			
High pressure hose pipe cleaning DN6 14M	38	6.392-632.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). <input type="checkbox"/>
	39	6.392-633.0	30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). <input type="checkbox"/>
Hose assembly TR pipe cleaning DN6 max.2	40	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). <input type="checkbox"/>
Pipe cleaning hose	41	6.390-028.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). <input type="checkbox"/>
Pipe cleaning hose, DN 6, 20 m, 220 bar	42	6.110-008.0	<input type="checkbox"/>

Available accessories.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0



		Order no.	Description	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Pipe cleaning hose, DN 6, 30 m	43	6.390-029.0	30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	<input type="checkbox"/>
Hose assembly TR pipe cleaning DN6 max.2	44	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Pipe cleaning hose, DN 6, 20 m, 220 bar	45	6.390-030.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
FRV 30	46	2.642-999.0	With the integrated and automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient. There is no longer a need to rinse the surface after cleaning, as the dirty water can be removed through the 5m suction hose, which is supplied. Additional features include the non-marking steering rollers and double ceramic bearings. Machine specific nozzle kit must be ordered separately.	<input type="checkbox"/>
Add-on kit rubber lip	47	2.642-910.0	For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	<input type="checkbox"/>
Extension hose 5 m	48	4.440-939.0	5m extension hose for FRV 30. Connection sleeve included.	<input type="checkbox"/>
Add-on kit hose attachment	49	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	<input type="checkbox"/>
Add-on kit dirt trap	50	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	<input type="checkbox"/>
Hard surface cleaner FR 30 ME				
FR 30 ME surface cleaner	51	2.640-355.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
Hard Surface Cleaner FR 50				
FR 50 surface cleaner	52	2.640-679.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	<input type="checkbox"/>
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 650 l/h - 850 l/h	53	2.639-187.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (650 to 850 l/h).	<input type="checkbox"/>
Machine-specific nozzle kits for FRV				
Nozzle kit for FRV, 040	54	2.642-431.0	Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for FRV 30.	<input type="checkbox"/>
Hard surface cleaner FRV 30 Me				
FRV 30 ME	55	2.642-911.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	<input type="checkbox"/>
Extension hose FRV 30 Me and FRV 50 Me	56	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	<input type="checkbox"/>

Available accessories.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0



		Order no.	Description	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Advanced	57	6.394-969.0	Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	<input type="checkbox"/>
Inno Foam Set				
Inno foam kit with detergent injector	58	2.640-151.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	<input type="checkbox"/>
Easy Foam Set				
Easy Foam Set with RM injector	59	2.640-691.0	HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	<input type="checkbox"/>
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 090 Inno/Easy kit 700 - 1000 l/h	60	2.640-688.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.	<input type="checkbox"/>
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high pressure	61	3.637-170.0	Cleaning agent dosage at high pressure 3 - 5 %	<input type="checkbox"/>
Detergent injector for high and low pressure (without nozzles)	62	3.637-001.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	<input type="checkbox"/>
Machine-specific nozzle kit with order no. 3.637-170				
Nozzle insert trapezoidal thread HDS-GER	63	4.769-011.0	For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	<input type="checkbox"/>
Machine-specific nozzle kit with order no. 3.637-170.0 750-1000 l/h	64	4.769-047.0		<input type="checkbox"/>
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	65	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	<input type="checkbox"/>
Low pressure for units rated up to 1100 l/h	66	4.769-001.0	For low pressure with machines up to 1.100 l/h	<input type="checkbox"/>
COUPLING PARTS				
Rotary coupling				
Rotary coupling	67	4.401-091.0	Reliably prevents twisting of HP hoses. Connection M 22 × 1.5 m. Handle protection	<input type="checkbox"/>
Coupling				
Coupler -2xM22x1,5	68	4.403-002.0	For connecting and extending high-pressure hoses. Connection 2 × M 22 × 1.5.	<input type="checkbox"/>
Connector				
Nozzle connector/screw connector	69	4.402-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 × 1.5 and 1x M 18 × 1.5.	<input type="checkbox"/>
Adapter				
Adapter M22 - Swivel	70	4.424-004.0	In order to install high-pressure hose with male coupling on thread with M22 × 1.5 Alternative:4.111-032.0 Adapter 4 - Device new / Hose old Swivel	<input type="checkbox"/>

Available accessories.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0



		Order no.	Description	
COUPLING PARTS				
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	71	4.111-029.0	Adapter 1 to connect the old hose with the new hose	<input type="checkbox"/>
Adapter 2 M22IG-TR22AG	72	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	<input type="checkbox"/>
Adapter 3 M22IG-TR22AG	73	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	<input type="checkbox"/>
Adapter 5 TR22IG-M22AG	74	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	<input type="checkbox"/>
Adapter 6 TR22IG-M22AG	75	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	<input type="checkbox"/>
Adapter 7 M18IG-TR20AG	76	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	<input type="checkbox"/>
Adapter 8 TR20IG-M18AG	77	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	<input type="checkbox"/>
HOSE REELS				
Automatic, self-winding hose reels				
Automatic stainless steel hose reel, 40 m	78	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	<input type="checkbox"/>
FACADE AND SOLAR PANEL CLEANING				
Brushes				
iSolar 800 Advanced	79	6.368-094.0	iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.	<input type="checkbox"/>
iSolar 400 Advanced	80	6.368-092.0	iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.	<input type="checkbox"/>
Wasserenthärtung				
WS 50	81	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	<input type="checkbox"/>
WS 100	82	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	<input type="checkbox"/>
WS Regenerator	83	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	<input type="checkbox"/>
Hoses				
Hose solar	84	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	<input type="checkbox"/>

Available accessories.

EQUIPMENT FOR HD 8/23 G CLASSIC

1.187-012.0



	Order no.	Description	
FACADE AND SOLAR PANEL CLEANING			
Hoses			
Hose solar	85	6.392-977.0 High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	<input type="checkbox"/>
	86	6.392-976.0 High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	<input type="checkbox"/>
Attachment kits and adapters			
Case sheet steel	87	6.988-152.0 Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	<input type="checkbox"/>
WET BLASTING ATTACHMENT			
Wet blasting attachment (without nozzle)			
Wet blasting attachment with flow control (without nozzles)	88	4.762-010.0 Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	<input type="checkbox"/>
Wet blasting attachment without flow control (nozzles not included)	89	4.762-022.0 Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling. Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation	<input type="checkbox"/>
Nozzle pack for wet blasting attachment			
Nozzle kit for wet blasting attachment 040	90	2.637-900.0 Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.	<input type="checkbox"/>
Boron carbide nozzle			
Boron carbide nozzle, for machines as of 1000 l/h	91	6.415-084.0 In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	<input type="checkbox"/>
WATER CONNECTION			
Geka coupling			
With hose nozzle, R 3/4"	92	6.388-455.0 with hose liner	<input type="checkbox"/>
Fine-mesh water filter			
Add-on kit water filter universal	93	2.637-020.0 Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	<input type="checkbox"/>
Fine-mesh water filter with adapter	94	4.730-102.0 Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
WASHING BRUSHES			
Push-on washing brush			
Push-on wash brush, M 18 × 1.5	95	4.113-001.0 For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection	<input type="checkbox"/>
	96	4.762-016.0 For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18 × 1.5	<input type="checkbox"/>
DRUM AND TANK CLEANING			
Barrel and tank cleaning			
Rotary cleaner head M63E	97	6.751-061.0 Compact interior cleaning head made of stainless steel for cleaning the interiors of drums and containers with openings of 65 mm or more. Offers an impressively low weight and constant rotation speed by means of an electric motor.	<input type="checkbox"/>

Available accessories.