# HD 10/21-4 S

The HD 10/21-4 S cold water high-pressure cleaner in an upright construction style impresses with EASY!Force high-pressure gun, pressure switch control and a rotatable stainless steel spray lance.



WORLD'S NO. 1 PRESSURE WASHER BRAND

Made in Germany

3–4 h

EASY!Force

ANTI-TWIST

| Order no. | 1.286-916.0 |
|---|---|

- Save time and energy: EASY!Force high-pressure gun and EASY!Lock quick-release fasteners
- Water-cooled three-phase motor
- Features Kärcher power nozzle

## Technical data

| | | |
|---|---|---|
| **EAN code** | | 4054278162966 |
| **Number of current phases** | **Ph** | 3 |
| **Voltage** | **V** | 400 |
| **Frequency** | **Hz** | 50 |
| **Flow rate** | **l/h** | 1000 |
| **Inlet temperature** | **°C** | up to 60 |
| **Working pressure** | **bar / MPa** | 210 / 21 |
| **Max. pressure** | **bar / MPa** | 231 / 23.1 |
| **Connected load** | **kW** | 8 |
| **Colour** | | anthracite |
| **Weight (with accessories)** | **kg** | 62.8 |
| **Weight incl. packaging** | **kg** | 68.8 |
| **Dimensions (L × W × H)** | **mm** | 560 × 500 × 1090 |

**This machine requires instruction.**

## Scope of supply

**Spray gun:** EASY!Force Advanced
**Spray gun with soft grip padding**
**High-pressure hose length:** 10 m
**Spray lance:** 1050 mm
**Power nozzle**

## Equipment

**4-pole three-phase motor with air and water cooling**
**3-piston axial pump:** With ceramic pistons
**Pressure cut-off**
**Integrated water fine filter**
**Sight glass for oil level**
**Brass water inlet**

HD 10/21-4 S, 1.286-916.0, 2026-09-18






### Save time and energy: EASY!Force high-pressure gun and EASY!Lock quick-release fasteners

- Fatigue-free work at last: the EASY!Force high pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.



### Proven Kärcher quality

- 4-pole water-cooled electric motor.
- Robust brass cylinder head and ceramic piston.
- Reinforced, unbreakable plastic chassis.



### Water fine filter

- The large, integrated water fine filter reliably protects the high-pressure pump against small dirt particles.
- Protects the high-pressure pump against contamination and extends its service life

HD 10/21-4 S, 1.286-916.0, 2026-09-18

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


1


2


3


4


5


6


7


8


9


10


11


12


13


14

| | | Order no. | Description | |
|---|---|---|---|---|
| **TRIGGER GUNS** | | | | |
| **Spray guns** | | | | |
| EASY!Force Advanced | 1 | 4.118-005.0 | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. | ■ |
| EASY!Force conversion kit 1 – from high-pressure hose | 2 | 4.111-050.0 | For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle. | ☐ |
| EASY!Force conversion kit 2 – from machine | 3 | 4.111-051.0 | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. | ☐ |
| EASY!Force conversion kit 3 – high-pressure gun | 4 | 4.111-052.0 | Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. | ☐ |
| **Servo control** | | | | |
| Servo Control, 750 l/h – 1100 l/h | 5 | 4.118-008.0 | Water quantity and pressure regulated directly from the hand spray gun. | ☐ |
| **SPRAY LANCES** | | | | |
| **Rotating spray lances** | | | | |
| Spray lance, 1050 mm, rotatable | 6 | 4.112-000.0 | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ■ |
| Jet pipe with transport packaging, 840 mm | 7 | 4.119-003.0 | Rotating Classic spray lance with handle bowls in a stainless steel design. Also suitable for Kärcher hot water high-pressure cleaners. | ☐ |
| Jet pipe TR 600mm with package, 600 mm | 8 | 4.119-009.0 | | ☐ |
| Jet pipe Classic TR 100mm, 100 mm | 9 | 4.119-013.0 | | ☐ |
| Jet pipe Classic TR 200mm, 200 mm | 10 | 4.119-014.0 | | ☐ |
| Jet pipe Classic TR 400mm, 400 mm | 11 | 4.119-015.0 | | ☐ |
| LED nozzle light | 12 | 2.680-002.0 | Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours. | ☐ |
| Spray lance, 250 mm, rotatable | 13 | 4.112-027.0 | Spray lance, 250 mm, rotatable, ergonomic | ☐ |
| Spray lance, 400 mm, rotatable | 14 | 4.112-024.0 | Spray lance, 400 mm, rotatable, ergonomic | ☐ |

■ Included in the scope of supply. ☐ Available accessories.


KÄRCHER


# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


15


16


17


18


19


20


21


22


23


24


25


26


27–30

| | | Order no. | Description | |
|---|---|---|---|---|
| **SPRAY LANCES** | | | | |
| **Rotating spray lances** | | | | |
| Spray lance, 600 mm, rotatable | 15 | 4.112-007.0 | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ☐ |
| Spray lance, 840 mm, rotatable | 16 | 4.112-006.0 | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ☐ |
| Spray lance, 1550 mm, rotatable | 17 | 4.112-018.0 | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ☐ |
| Spray lance, 2050 mm, rotatable | 18 | 4.112-021.0 | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ☐ |
| Spray lance extender, 1000 mm | 19 | 4.112-048.0 | Spray lance extension with EASY!Lock connection. Length 1000 mm. | ☐ |
| **Double lance** | | | | |
| Double lance, 960 mm | 20 | 2.112-016.0 | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use ( e.g. stable cleaning). | ☐ |
| **Angular spray lance** | | | | |
| Spray lance for toilets and rain gutters | 21 | 4.112-029.0 | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | ☐ |
| **Flexible spray lance** | | | | |
| Flexible lance, 1050 mm | 22 | 4.112-035.0 | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | ☐ |
| High pressure articulated joint | 23 | 4.112-057.0 | For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer. | ☐ |
| **Gutter cleaner** | | | | |
| Gutter cleaning lance | 24 | 2.112-015.0 | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | ☐ |
| **Undercarriage spray lance** | | | | |
| Underbody lance | 25 | 4.112-032.0 | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | ☐ |
| **Additional handle** | | | | |
| Additional handle for EASY!Lock spray lances | 26 | 4.321-380.0 | Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility. | ☐ |
| **KÄRCHER POWER NOZZLE** | | | | |
| **Power nozzle spray angle 25°** | | | | |
| Power nozzle 25°, 052 | 27 | 2.113-024.0 | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. | ■ |
| **HP nozzle spray angle 0°** | | | | |
| Power nozzle 0°, 055 | 28 | 2.113-035.0 | High-pressure nozzle with powerful jet for extremely stubborn dirt. | ☐ |

■ Included in the scope of supply. ☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


27–30


31, 33–35


32, 36


37


38–39, 41


40


42

| | | Order no. | Description | |
|---|---|---|---|---|
| **KÄRCHER POWER NOZZLE** | | | | |
| **Power nozzle spray angle 15°** | | | | |
| Power nozzle 15°, 055 | 29 | 2.113-047.0 | Fan jet nozzle with 15° spray angle suitable for stubborn dirt. | ☐ |
| **Power nozzle spray angle 40°** | | | | |
| Power nozzle 40°, 055 | 30 | 2.113-055.0 | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. | ☐ |
| **HIGH-PRESSURE HOSES** | | | | |
| **Standard with unions on both sides** | | | | |
| High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock | 31 | 6.110-031.0 | High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long. | ■ |
| High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock | 32 | 6.110-041.0 | Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar. | ☐ |
| High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock | 33 | 6.110-030.0 | 15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides. | ☐ |
| High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock | 34 | 6.110-032.0 | High-pressure hose (DN 8) with a length of 20 m and EASY!Lock manual screw fitting on both sides. Approved for max. 315 bar pressure. | ☐ |
| High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock | 35 | 6.110-014.0 | Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar. | ☐ |
| High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock | 36 | 6.110-042.0 | Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10). | ☐ |
| High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock | 37 | 6.110-043.0 | 20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10). | ☐ |
| High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock | 38 | 6.110-044.0 | Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar. | ☐ |
| High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock | 39 | 6.110-045.0 | 40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar. | ☐ |
| High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock | 40 | 6.110-059.0 | Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides. | ☐ |
| High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock | 41 | 6.110-060.0 | With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar. | ☐ |
| **Longlife 400 with unions on both sides** | | | | |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × EASY!Lock | 42 | 6.110-024.0 | 1.5 m high-pressure hose (DN 8) with EASY!Lock manual screw fitting on both sides. Designed for max. 400 bar pressure. | ☐ |

■ Included in the scope of supply. ☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


43


44


45–47


48


49


50


51


52


53–54


55–56

| | | Order no. | Description | |
|---|---|---|---|---|
| **HIGH-PRESSURE HOSES** | | | | |
| **Longlife 400 with unions on both sides** | | | | |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5 | 43 | 6.110-069.0 | 1.5 m long high-pressure hose (DN 8) suitable for up to 400 bar pressure with double steel core. Connections: M 22 × 1.5, as well as the comfortable and quick EASY!Lock manual screw fitting. | ☐ |
| High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock | 44 | 6.110-038.0 | 10 m long high-pressure hose (DN 8) with double steel core, EASY!Lock manual screw fitting on both sides, and ANTI!Twist. Approved for max. 400 bar pressure. | ☐ |
| High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × EASY!Lock | 45 | 6.110-023.0 | High-pressure hose with double steel core, ANTI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, approved for max. 400 bar pressure. | ☐ |
| High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock | 46 | 6.110-027.0 | High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides. | ☐ |
| High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × EASY!Lock | 47 | 6.110-029.0 | The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar. | ☐ |
| **Food industry version with unions on both sides** | | | | |
| High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock | 48 | 6.110-051.0 | High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With EASY!Lock hand screw connection at both ends. | ☐ |
| High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × EASY!Lock | 49 | 6.110-052.0 | Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections. | ☐ |
| **Longlife food design with screw connections at both ends** | | | | |
| High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock | 50 | 6.110-053.0 | With blue, non-marking and animal fat-resistant outer covering: High-pressure hose (ID 8), 10 m long, with ANTI!Twist and EASY!Lock hand screw connection at both ends. | ☐ |
| High-pressure hose food grade Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock | 51 | 6.110-054.0 | High-pressure hose with double steel reinforcement and blue, non-marking and animal fat-resistant outer covering. 20 m long with EASY!Lock hand screw connections. | ☐ |
| **Special hoses** | | | | |
| High-pressure hose curved, 1.5 m, ID 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5 | 52 | 6.110-068.0 | For connection to hose reels: high-pressure hose, with M 22 × 1.5 connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure. | ☐ |
| **Classic** | | | | |
| Hose TR DN8 31,5MPa 20m with package, 20 m, ID 8, 315 bar × , EASY!Lock | 53 | 4.119-006.0 | High pressure hose with convenient EASY!Lock manual fitting from the Classic series by Kärcher. Also suitable for hot water high-pressure cleaners. | ☐ |
| Hose TR DN8 31,5MPa 30m with package, 30 m, ID 8, 315 bar × , EASY!Lock | 54 | 4.119-007.0 | | ☐ |
| Hose assembly with package TR DN10 25MPa, 20 m, ID 10, 250 bar × , EASY!Lock | 55 | 4.119-019.0 | | ☐ |
| Hose assembly with package TR DN10 25MPa, 40 m, ID 10, 250 bar × , EASY!Lock | 56 | 4.119-020.0 | | ☐ |

☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


57


58


59


60



61


62


63


65


67


68


69–71

| | | Order no. | Description | |
|---|---|---|---|---|
| **ROTARY NOZZLES (DIRT BLASTERS)** | | | | |
| **Dirt blaster, large** | | | | |
| Dirt blaster, large, 055/060 | 57 | 4.114-036.0 | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | ☐ |
| **Classic rotary nozzle** | | | | |
| Rotor nozzle TR 060 | 58 | 4.119-025.0 | The powerful rotating point jet of the Classic rotary nozzle from Kärcher ensures the best possible cleaning results and is suitable for water temperatures of up to 60 °C. | ☐ |
| **MULTIPLE-JET NOZZLES** | | | | |
| **Triple nozzles** | | | | |
| Triple nozzle, 053 | 59 | 4.117-038.0 | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application. | ☐ |
| **Angled vario nozzle 0-90°** | | | | |
| Angled Vario nozzle, 055 | 60 | 4.113-008.0 | Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces. | ☐ |
| **ECO!BOOSTER** | | | | |
| Eco!Booster MAX TR 080 | 61 | 2.113-099.0 | eco!Booster MAX: 100 percent higher area performance compared to the Kärcher standard flat jet nozzle. | ☐ |
| **QUICK CONNECT** | | | | |
| Quick coupling | 62 | 2.115-000.0 | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread. | ☐ |
| Male coupling | 63 | 2.115-001.0 | Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 × 1.5 external thread. | ☐ |
| **DRUM AND TANK CLEANING** | | | | |
| Add-on kit mud sucker | 64 | 2.641-798.0 | For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps. | ☐ |
| **OTHER HP ACCESSORIES** | | | | |
| Jet gun | 65 | 2.869-067.0 | Spray lance with immediate shut-off and infinitely variable pressure and water volume control. | ☐ |
| **SEALS FOR TRAPEZOIDAL THREAD** | | | | |
| Gasket set with 9x O-rings for TR thread | 66 | 2.880-001.0 | | ☐ |
| **STEAM JET NOZZLE / NOZZLE PROTECTOR / ROLLOVER NOZZLE** | | | | |
| **Rollover nozzle holder** | | | | |
| Owner of jets double brass | 67 | 4.764-012.0 | Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle). | ☐ |
| **NOZZLE UNION / SPACER** | | | | |
| **Nozzle union** | | | | |
| Nozzle screws | 68 | 4.112-011.0 | Nozzle screws with protectors for high-pressure and power nozzles | ☐ |
| **PIPE CLEANING** | | | | |
| **Pipe cleaning hose, ID 6** | | | | |
| Pipe cleaning hose, ID 6, 10 m, max. 250 bar | 69 | 6.110-046.0 | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | ☐ |
| Pipe cleaning hose, ID 6, 20 m, max. 250 bar | 70 | 6.110-008.0 | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | ☐ |

☐ Available accessories.

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


69–71


72


73


74


75–76


77


78


79


80


81


83, 91


84

| | | Order no. | Description | |
|---|---|---|---|---|
| **PIPE CLEANING** | | | | |
| **Pipe cleaning hose, ID 6** | | | | |
| Pipe cleaning hose, ID 6, 30 m, max. 250 bar | 71 | 6.110-047.0 | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | ☐ |
| **Pipe cleaning nozzle** | | | | |
| Pipe cleaning dirt blaster D21/060 | 72 | 4.765-002.0 | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | ☐ |
| Pipe cleaning dirt blaster D30/060 | 73 | 4.765-005.0 | | ☐ |
| Pipe cleaning nozzle 080 | 74 | 5.763-087.0 | Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle. | ☐ |
| Pipe cleaning nozzle | 75 | 5.763-019.0 | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for cleaning blocked drains and pipes. | ☐ |
| | 76 | 5.763-016.0 | | ☐ |
| | 77 | 5.763-021.0 | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for cleaning blocked drains and pipes. | ☐ |
| Rotating pipe cleaning nozzle | 78 | 6.415-440.0 | Rotating pipe cleaning nozzle with internal thread and four rotating jets for cleaning blocked drains and pipes. | ☐ |
| **FLOOR AND HARD SURFACE CLEANER** | | | | |
| **FR Classic surface cleaner** | | | | |
| FR TR 40 Classic | 79 | 4.119-029.0 | The classic surface cleaner with 400 mm diameter and nozzle kit supplied (2 × size 020; others can be ordered separately). | ☐ |
| FR TR 30 Classic | 80 | 4.119-030.0 | The classic surface cleaner with 300 mm diameter and nozzle kit supplied (2 × size 018; others can be ordered separately). | ☐ |
| **Hard Surface Cleaner FRV 30** | | | | |
| FRV 30 Surface Cleaner | 81 | 2.111-010.0 | Integrated automatic suction removes dirty water through the supplied 5 m suction hose, eliminating the need to rinse the surface after cleaning and allowing use in inside and outside areas. Features include non-marking steering rollers and double ceramic bearings. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1000 l/h / 60 °C. | ☐ |
| Rubber lip for FRV 30 | 82 | 2.642-910.0 | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes. | ☐ |
| Extension hose 5 m | 83 | 4.440-939.0 | 5m extension hose for FRV 30. Connection sleeve included. | ☐ |
| Hose fastening attachment kit | 84 | 2.642-528.0 | Suction cup for fixing the suction hose to smooth surfaces. | ☐ |

☐ Available accessories.


KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


85


86


87


88


89


90


83, 91


92


93


94


95


96


97


98

| | | Order no. | Description | |
|---|---|---|---|---|
| **FLOOR AND HARD SURFACE CLEANER** | | | | |
| **Hard Surface Cleaner FRV 30** | | | | |
| Dirt trap attachment kit | 85 | 2.642-532.0 | Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. | ☐ |
| **FR 30 Me surface cleaner** | | | | |
| Hard Surface Cleaner FR 30 Me | 86 | 2.111-013.0 | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | ☐ |
| **Hard Surface Cleaner FR 50** | | | | |
| Surface Cleaner FR 50 Me | 87 | 2.111-023.0 | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. | ☐ |
| **Machine-specific nozzle kits for FR** | | | | |
| Nozzle kit for FR, 850 l/h – 1100 l/h | 88 | 2.640-442.0 | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h). | ☐ |
| **Machine-specific nozzle kits for FRV** | | | | |
| Nozzle kit for FRV, 050 | 89 | 2.642-433.0 | Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. | ☐ |
| **FRV 30 Me surface cleaner** | | | | |
| FRV 30 Me Surface Cleaner | 90 | 2.111-012.0 | The stainless steel FRV 30 Me Surface Cleaner is designed for hot water cleaning up to 85 °C in inside and outside areas. Integrated automatic suction removes dirty water directly during operation. | ☐ |
| Extension hose FRV 30 Me and FRV 50 Me | 91 | 4.441-040.0 | 5 m extension hose for FRV 30 Me. Includes connecting adapter. | ☐ |
| **Surface Cleaner FR 50 Me** | | | | |
| FRV 50 Me surface cleaner | 92 | 2.111-024.0 | Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. | ☐ |
| **FOAM SYSTEMS** | | | | |
| **Cup foam lance** | | | | |
| Cup foam lance Advanced 3, 900 l/h – 2500 l/h | 93 | 4.112-065.0 | Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. | ☐ |
| Cup foam lance DUO Advanced 3, 900 l/h – 2500 l/h | 94 | 4.112-069.0 | DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. | ☐ |
| Cup foam lance Basic 3, 900 l/h – 2500 l/h | 95 | 4.112-055.0 | Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900–2500 l/h: Reduces cleaning agent consumption by 50% compared to cup foam lances without a dosing facility. | ☐ |
| 1-litre cleaning agent container for cup foam lance basic | 96 | 5.071-414.0 | For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). | ☐ |
| 1-litre cleaning agent container for cup foam lance advanced | 97 | 6.414-050.0 | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0). | ☐ |
| **Inno Foam Kit** | | | | |
| Inno Foam Set with detergent injector | 98 | 2.112-000.0 | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. | ☐ |

☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


99


100


101


102


103


104


105


106–107


108


109


110


111


112

| | | Order no. | Description | |
|---|---|---|---|---|
| **FOAM SYSTEMS** | | | | |
| **Easy Foam Set** | | | | |
| Easy Foam Set with RM injector | 99 | 2.112-010.0 | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | ☐ |
| **Nozzle kits for Inno/Easy Foam Set** | | | | |
| Nozzle kit 090 for Inno / Easy Set 700–1,000 l/h | 100 | 2.111-019.0 | Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance. | ☐ |
| **Foam nozzle mounting kit** | | | | |
| Foam nozzle attachment kit | 101 | 2.112-013.0 | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. | ☐ |
| **MIXERS AND INJECTORS** | | | | |
| **Cleaning agent injector** | | | | |
| Cleaning agent injector for high and low pressure (without nozzles) | 102 | 4.637-032.0 | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%. | ☐ |
| Cleaning agent injector for high pressure (without nozzle) | 103 | 4.637-033.0 | Cleaning agent dosage at high pressure 3 – 5 % | ☐ |
| Stainless steel injector kit for HD 10/25-4S | 104 | 6.645-761.0 | Stainless steel injector for cleaning agent and foam applications. Specifically for the HD 10/25-4 S High-pressure cleaner. For precise cleaning agent dosage. | ☐ |
| **Machine-specific nozzle kit with order no. 4.637-033.0** | | | | |
| Nozzle kit 750–1000 l/h | 105 | 4.769-011.0 | For HD/HDS 750 – 1000 l/h. Consists of nozzle insert + HP power nozzle + union | ☐ |
| **Nozzle insert with order no. 4.637-032.0** | | | | |
| Nozzle insert up to 1,100 l/h – high pressure | 106 | 4.769-003.0 | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h. | ☐ |
| Nozzle insert up to 1,100 l/h – low pressure | 107 | 4.769-001.0 | For low pressure with machines up to 1.100 l/h | ☐ |
| **COUPLING PARTS** | | | | |
| **Rotary coupling** | | | | |
| Rotary coupling | 108 | 4.111-021.0 | Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection | ☐ |
| **Connector** | | | | |
| Screw socket for surface cleaners and Servo Control controllers | 109 | 4.111-022.0 | For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) – 1 × M 22 × 1.5/1 × M 18 × 1.5. | ☐ |
| Y distributor | 110 | 4.111-024.0 | Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. | ☐ |
| Short spray unit | 111 | 4.111-038.0 | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles. | ☐ |
| **EASY!Lock adapter** | | | | |
| Adapter 1 M22AG-TR22AG | 112 | 4.111-029.0 | Adapter 1 to connect the old hose with the new hose | ☐ |

☐ Available accessories.

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


113


114


115


116


117


118


119


120


121


122


123


124


125


126

| | | Order no. | Description | |
|---|---|---|---|---|
| **COUPLING PARTS** | | | | |
| **EASY!Lock adapter** | | | | |
| Adapter 2 M22IG-TR22AG | 113 | 4.111-030.0 | Adapter 2 to connect the old device with the new hose and the old gun with the new hose | ☐ |
| Adapter 3 M22IG-TR22AG | 114 | 4.111-031.0 | Adapter 3 to connect the old gun with the new spray lance and new servo regulator | ☐ |
| Adapter 4 TR22IG-D11 | 115 | 4.111-032.0 | Adapter 4 to connect the new gun with the old swivel hose | ☐ |
| Adapter 5 TR22IG-M22AG | 116 | 4.111-033.0 | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance | ☐ |
| Adapter 6 TR22IG-M22AG | 117 | 4.111-034.0 | Adapter 6 to connect the new device with the old hose and the old hose with the new gun | ☐ |
| Adapter 7 M18IG-TR20AG | 118 | 4.111-035.0 | Adapter 7 to connect the old spray lance with the new nozzle | ☐ |
| Adapter 8 TR20IG-M18AG | 119 | 4.111-036.0 | Adapter 8 to connect the new spray lance with the old nozzle | ☐ |
| Adapter hose extension 9 TR | 120 | 4.111-037.0 | Adapter 9 to connect the new hose with the new hose | ☐ |
| Adapter 12 rotary coupling EASY!Lock 22 IG – M22 × 1.8 AG | 121 | 4.111-046.0 | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection | ☐ |
| **HOSE REELS** | | | | |
| **Manual hose reel attachment kit** | | | | |
| Hose reel attachment kit for HD super class, 20 m | 122 | 2.110-008.0 | Hose reel attachment kit for installation on the machine. For secure and space-saving storage of the high-pressure hose (with a connection hose for the machine HP output). Rotatable under pressure with connection 22 × 1.5. | ☐ |
| **Automatic, self-winding hose reels for wall mounting** | | | | |
| Automatic plastic hose reel incl. high-pressure hose, 15 m | 123 | 2.639-257.0 | Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety. | ☐ |
| Automatic hose reel, powder-coated steel / plastic, 20 m | 124 | 6.392-074.0 | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | ☐ |
| Automatic stainless steel / synthetic material hose drum, 20 m | 125 | 6.392-083.0 | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | ☐ |
| Automatic hose reel, coated, 20 m | 126 | 6.392-106.0 | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | ☐ |


☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


127


129


130–131


132


133


134


135


136


137


138


139


140

| | | Order no. | Description | |
|---|---|---|---|---|
| **HOSE REELS** | | | | |
| **Automatic, self-winding hose reels for wall mounting** | | | | |
| Hose reel, automatic, basalt grey-coated, 20 m | 127 | 6.392-105.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife). | ☐ |
| Automatic hose reel, stainless steel, includes swivel holder, 20 m | 128 | 6.392-076.0 | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | ☐ |
| Automatic stainless steel hose reel, 40 m | 129 | 6.392-442.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit). | ☐ |
| Zinc-coated swivel holder | 130 | 2.639-931.0 | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. | ☐ |
| Stainless steel swivel holder | 131 | 2.641-867.0 | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. | ☐ |
| **FACADE AND SOLAR PANEL CLEANING** | | | | |
| **Brushes** | | | | |
| Drive for roller brush 500 | 132 | 4.762-584.0 | Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance. | ☐ |
| Splash guard for roller brush 500 | 133 | 4.762-621.0 | Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time. | ☐ |
| Roller brush 500 soft | 134 | 4.762-623.0 | Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive. | ☐ |
| Roller brush 500 medium | 135 | 4.762-624.0 | Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system. | ☐ |
| Roller brush 500 hard | 136 | 4.762-625.0 | Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system. | ☐ |
| Brush hard | 137 | 6.960-133.0 | Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher. | ☐ |
| Brush medium | 138 | 6.960-134.0 | Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher. | ☐ |
| Brush soft | 139 | 6.960-135.0 | For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems. | ☐ |
| iSolar 800 Advanced | 140 | 6.368-094.0 | iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems. | ☐ |

☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


141


142


143–144


145–146


147


148


149–15


152–154

| | | Order no. | Description | |
|---|---|---|---|---|
| **FACADE AND SOLAR PANEL CLEANING** | | | | |
| **Brushes** | | | | |
| iSolar 400 Advanced | 141 | 6.368-092.0 | iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems. | ☐ |
| **Telescopic lances** | | | | |
| TL low pressure adapter | 142 | 4.580-097.0 | TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes. | ☐ |
| Telescopic lance TL 7 F | 143 | 4.762-609.0 | Telescopic lance TL 7 F with 7 m reach made from lightweight glass fibre. With quick-release fasteners for retraction and extension. | ☐ |
| Telescopic lance TL 7 H | 144 | 4.762-610.0 | Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach. | ☐ |
| Telescopic lance TL 10 H | 145 | 4.762-611.0 | Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners. | ☐ |
| Telescopic lance TL 10 C | 146 | 4.762-612.0 | Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels. | ☐ |
| Telescopic lance TL 14 C | 147 | 4.762-613.0 | Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners. | ☐ |
| TL high pressure adapter | 148 | 4.775-154.0 | TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals. | ☐ |
| **Water softening** | | | | |
| WS 50 | 149 | 6.368-463.0 | The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water. | ☐ |
| WS 100 | 150 | 6.368-464.0 | The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water. | ☐ |
| WS Regenerator | 151 | 6.368-465.0 | With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button. | ☐ |
| **Hoses** | | | | |
| iSolar HP hose 7 | 152 | 6.392-978.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | ☐ |
| iSolar HP hose 10 | 153 | 6.392-977.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | ☐ |
| iSolar HP hose 14 | 154 | 6.392-976.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | ☐ |

☐ Available accessories.

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


155


156–157


158


159


160


161


162–163


164


165


166


167


168

| | | Order no. | Description | |
|---|---|---|---|---|
| **FACADE AND SOLAR PANEL CLEANING** | | | | |
| **Attachment kits and adapters** | | | | |
| iSolar fall protection | 155 | 6.988-152.0 | Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case. | ☐ |
| **WET BLASTING ATTACHMENT** | | | | |
| **Wet blasting attachment (without nozzle)** | | | | |
| Wet blasting attachment with flow control (without nozzles) | 156 | 4.115-000.0 | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. | ☐ |
| Wet blasting attachment without flow control (nozzles not included) | 157 | 4.115-006.0 | Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling. Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation | ☐ |
| **Nozzle kits for wet jet unit** | | | | |
| Nozzle kit for wet jet unit 050 | 158 | 2.112-023.0 | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment . | ☐ |
| **Boron carbide nozzle** | | | | |
| Boron carbide, for machines from 1,000 l/h | 159 | 6.415-083.0 | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. | ☐ |
| **DRUM AND TANK CLEANING** | | | | |
| **Barrel and tank cleaning** | | | | |
| Barrel cleaner BC 14/12 | 160 | 2.112-020.0 | The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres. | ☐ |
| Spray head HKF 30/14-E | 161 | 6.751-061.0 | Compact interior cleaning head made of stainless steel for cleaning the interiors of drums and containers with openings of 65 mm or more. Offers an impressively low weight and constant rotation speed by means of an electric motor. | ☐ |
| **Nozzle kit for spray head HKF 50 (3.631-009.0 / 3.631-039.0)** | | | | |
| Nozzle 045 for 2-nozzle operation HKF 50 | 162 | 6.415-446.0 | Nozzle for dual-nozzle operation | ☐ |
| High-pressure full jet nozzle 090 for interior cleaning heads | 163 | 6.415-447.0 | High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread. | ☐ |
| Double grip for precise control of spray head | 164 | 2.863-036.0 | Double handle. Precise control of the spray head | ☐ |
| 1/8" screw plug for interior cleaning heads | 165 | 5.411-061.0 | Screw plug for high-pressure interior cleaning heads with 1/8-inch thread. | ☐ |
| **WATER CONNECTION** | | | | |
| **Geka coupling** | | | | |
| Geka connector with hose barb, R 1" | 166 | 6.388-465.0 | with hose barb | ☐ |
| Geka connector with internal thread, R 1" | 167 | 6.388-458.0 | with female thread | ☐ |
| **Suction filter** | | | | |
| Water suction filter | 168 | 6.414-956.0 | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve | ☐ |

☐ Available accessories.

KÄRCHER

# ACCESSORIES FOR HD 10/21-4 S
# 1.286-916.0


169


171


172


173–174


175


176


177

| | | Order no. | Description | |
|---|---|---|---|---|
| **WATER CONNECTION** | | | | |
| **Suction filter** | | | | |
| Suction filter with check valve | 169 | 4.730-012.0 | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | ☐ |
| **Water fine filter** | | | | |
| Universal water fine filter, 25 µm | 170 | 2.637-020.0 | Fine water filter, mesh size 25 µm, max. temperature 50° C. Protects the device from dirt particles in the water. Maximum flow rate: 1,200 l/h. Connection 3/4", including 1" adapter. | ☐ |
| Water fine filter, with adapter | 171 | 4.730-102.0 | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | ☐ |
| Water fine filter, 100 µm, R 1" | 172 | 2.638-270.0 | Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1". | ☐ |
| **Water supply hose** | | | | |
| Water supply hose | 173 | 4.440-207.0 | NW 19 R1" / R 3/4", up to 85 °C, for pick-up | ☐ |
| | 174 | 4.440-270.0 | NW 19 R1" / R1", up to 85 °C | ☐ |
| **WASHING BRUSHES** | | | | |
| **Push-on washing brush** | | | | |
| Push-on wash brush | 175 | 4.113-001.0 | For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection | ☐ |
| **Rotating washing brush** | | | | |
| Rotating wash brush for > 1000 l/h machines, nylon bristles | 176 | 4.113-002.0 | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 × 1.5 (replaceable brush insert). | ☐ |
| Rotating wash brush for > 800 l/h machines, natural bristles | 177 | 4.113-005.0 | | ☐ |

☐ Available accessories.