OS 5.320 SV OSCILLATING SPRINKLER

OS 5.320 SV oscillating sprinkler with adjustable width of spray and splash guard for convenient alignment. For medium-sized/large surfaces up to 320 m2. Adjustable water volume (0-max.)

Order no.	2.645-135.0

Technical data		
EAN code		4039784426351
Sprinkling area 2 bar		20 - 190 m²
Sprinkling area 4 bar		30 - 320 m²
Width of spray 2 bar	m	5 - 12
Width of spray 4 bar	m	6 - 16
Area coverage 2 bar	m	5 - 16
Area coverage 4 bar	m	6 - 20
Colour		Black
Weight	kg	0.8
Weight incl. packaging	kg	0.9
Dimensions (L × W × H)	mm	546 × 160 × 88

Continuous reach adjustment

- Precise watering.

Loop for hanging the device integrated into the handle

- For simple storage/hanging.

Adjustable width of spray

- Different spray angles for targeted watering.

COMPATIBLE MACHINES

- HBX 4.15 Automatic
- HBX 4.20 Automatic
- HBX 5.25 Automatic
- HBX 5.30 Automatic
- HBX 5.35 Automatic
- HR 2.10 Set
- HR 3
- HR 3.20 Set
- HR 4
- HR 4.30 Set
- HT 2
- HT 2.20 Set
- HT 3
- HT 3.20 Set
- HT 4
- HT 4.20 Set
- HT 5 M
- HT 5.20 M Set
- HT 6 M
- Hose hanger
- Hose hanger Plus

OS 5.320 SV oscillating sprinkler, 2.645-135.0, 2026-10-23

EQUIPMENT FOR OS 5.320 SV OSCILLATING SPRINKLER 2.645-135.0

1

2

3

4

		Order no.	Description	
HOSES				
PrimoFlex® Premium hose 1/2" – 20 m	1	2.645-150.0	20 m PrimoFlex® Premium quality garden hose (1/2"). With patented dual-reinforcement technology. Contains no substances that are harmful to health. Bursting pressure: 50 bar. High temperature resistance from -20 to 65 °C.	☐
CONNECTORS/TAP ADAPTORS				
Premium universal hose coupling	2	2.645-195.0	Premium universal hose coupling made of metal. Comes with a robust hose clamp made of corrosion-free aluminium and soft plastic recessed grips. Compatible with all click systems.	☐
Premium universal hose coupling with Aqua Stop	3	2.645-196.0	Premium universal hose coupling made of metal. Comes with Aqua Stop and a robust hose clamp made of corrosion-free aluminium and soft plastic recessed grips. Compatible with all click systems.	☐
G3/4 tap adaptor with G1/2 reducer	4	2.645-006.0	Extremely tough tap connector 3/4" thread with 1/2" thread reducer. The reducer allows connection to two thread sizes. Compatible with all click systems.	☐

☐ Available accessories.