ROTARY CLEANER HEAD M63E

Compact interior cleaning head made of stainless steel for cleaning the interiors of drums and containers with openings of 65 mm or more. Offers an impressively low weight and constant rotation speed by means of an electric motor.



Order no.	6.751-061.0

Technical data		
EAN code		4066529072269
High-pressure connection		G3/8"
Drive		Electric
Number of nozzles	Piece(s)	1 / 4
Capacity	l/h	3000
Speed	rpm	19
Installation length	mm	915
Voltage	V	24
Frequency	Hz	50 - 60
Pressure	bar	max. 140
Tank opening	mm	min. 65
Temperature	°C	max. 90
Weight	kg	4.9
Weight incl. packaging	kg	7.6
Dimensions (L × W × H)	mm	1256





Driven by a 24 V 50/60 Hz electric motor.

- Constant rotational speed irrespective of the water flow rate or water pressure.
- 24 V safety voltage
- Increased work safety.



High flexibility

- Slow rotation and high working pressure for an optimal cleaning result.
- Suitable for water volumes up to 3000 l/h and high pressure up to 140 bar.
- Suitable for cleaning interiors of barrels, as well as medium-sized tanks and larger tanks too.



Intelligent design

- Easily accessible components simplify maintenance and servicing.
- Easy handling – One-handed operation of the head in the container.
- Regular rotation speed for consistent cleaning results.

Rotary cleaner head M63E, 6.751-061.0, 2026-10-30

COMPATIBLE MACHINES

- Cold Water Pressure Washer HD 6/11-4 M Plus 110v
- HD 10/15-4 Cage Food
- HD 10/16-4 Cage Ex (ATEX)
- HD 10/21-4 S Plus
- HD 10/21-4St
- HD 10/25-4 S
- HD 10/25-4 S Classic
- HD 10/25-4 S ST Classic
- HD 20/15-4 Cage Plus
- HD 7/12-4 M Plus
- HD 8/18-4 St
- HD 8/18-4St H
- HD 8/23 G Classic
- HD 9/20-4 SXA Plus
- HD 9/23 De
- HD 9/23 G
- HD 9/25 G Classic
- HDS 10/21 -4 St EU-I
- HDS 10/21 -4 St Gas -EU-I
- HDS 10/21-4 Classic
- HDS 10/21-4 M
- HDS 10/21-4 MXA
- HDS 1000 BE
- HDS 1000 DE
- HDS 13/20-4 S
- HDS 7/16 C
- HDS 8/20 De
- HDS 8/20 G
- HDS 9/20-4 Classic
- HDS 9/20-4 M
- HDS-E 8/16-4 M 12 kW
- HDS-E 8/16-4 M 24 kW
- HDS-E 8/16-4 M 36 kW

Rotary cleaner head M63E, 6.751-061.0, 2026-10-30

KÄRCHER

EQUIPMENT FOR ROTARY CLEANER HEAD M63E
6.751-061.0


1


2–4


5


6, 12, 20


7


8


9


10, 15, 17, 22


11, 14, 16, 18


13, 30, 36–37

		Order no.	Description	
DRUM AND TANK CLEANING				
Nozzle kit for HKF 50 spray head (3.631-009.0 / 3.631-039.0)				
Screw plug for using a spray head with one nozzle	1	5.411-061.0	Screw plug for high-pressure interior cleaning heads with 1/8-inch thread.	■
Nozzle 030 for dual nozzle operation HKF 50	2	6.415-444.0	High-pressure full jet nozzle 030 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread.	☐
Nozzle 045 for dual nozzle operation HKF 50	3	6.415-446.0	Nozzle for dual-nozzle operation	☐
Nozzle 090 for single nozzle operation HKF 50	4	6.415-447.0	High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread.	☐
Barrel and tank cleaning				
Add-on kit Control transformer	5	2.644-481.0	Electrical cabinet with control transformer (nominal power 100 VA) and 10 m cord (with plug) for the HKF 30/14-E interior cleaning head.	☐
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock	6	6.110-041.0	Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	☐
High-pressure hose, 10 m, ID 6, 250 bar, 2 × EASY!Lock	7	6.110-034.0	10 m long high-pressure hose with EASY!Lock manual screw fitting on both sides. Nominal size DN 6, suitable up to 250 bar.	☐
High-pressure hose, 10 m, ID 8, 315 bar, 2 × M22 × 1.5	8	6.391-342.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	☐
High-pressure hose, 15 m, ID 8, 315 bar, 2 × M22 × 1.5	9	6.390-010.0	With screw connections on both sides, M 22 × 1.5 with bend protection.	☐
High-pressure hose, 20 m, ID 8, 315 bar, 2 × M22 × 1.5	10	6.390-031.0	Screw connections at both ends, M 22 × 1.5, with kink protection.	☐
High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock	11	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long.	☐
High-pressure hose, 15 m, ID 8, 315 bar	12	6.110-033.0	15 m high-pressure hose, DN 8, fitted with EASY!Lock manual screw connections at both ends.	☐
High-pressure hose, 30 m, ID 8, 315 bar, 2 × M22 × 1.5	13	6.390-293.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	☐
High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock	14	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	☐

■ Included in delivery. ☐ Available accessories.

KÄRCHER

EQUIPMENT FOR ROTARY CLEANER HEAD M63E
6.751-061.0


10, 15, 17, 22


11, 14, 16, 18


19


6, 12, 20


21, 25


23, 27


24, 26, 28

		Order no.	Description	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 15 m, ID 10, 220 bar, 2 × M22 × 1.5	15	6.390-023.0	Connectors at both ends, M 22 × 1.5, with kink protection.	☐
High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock	16	6.110-032.0	High-pressure hose (DN 8) with a length of 20 m and EASY!Lock manual screw fitting on both sides. Approved for max. 315 bar pressure.	☐
High-pressure hose, 20 m, ID 10, 220 bar, 2 × M22 × 1.5	17	6.390-726.0	with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar	☐
High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock	18	6.110-014.0	Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar.	☐
High-pressure hose, 25 m, ID 10, 220 bar, 2 × M22 × 1.5	19	6.391-513.0	with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar	☐
High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock	20	6.110-042.0	Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10).	☐
High-pressure hose, 40 m, ID 10, 220 bar, 2 × M22 × 1.5	21	6.391-510.0	with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar	☐
High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock	22	6.110-043.0	20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	☐
High-pressure hose, 15 m, ID 12, 210 bar, 2 × M22 × 1.5	23	6.391-849.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 × 1.5 with anti-kink protection.	☐
High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock	24	6.110-044.0	Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	☐
High-pressure hose, 40 m, ID 12, 210 bar, 2 × M22 × 1.5	25	6.391-865.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 × 1.5 with anti-kink protection.	☐
High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock	26	6.110-045.0	40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	☐
High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock	27	6.110-059.0	Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	☐
High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock	28	6.110-060.0	With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	☐

☐ Available accessories.

KÄRCHER

EQUIPMENT FOR ROTARY CLEANER HEAD M63E
6.751-061.0


29


13, 30, 36–37


31, 33, 35, 46


32, 47


34


38


39


40–41


42

		Order no.	Description	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock	29	6.110-038.0	10 m long high-pressure hose (DN 8) with double steel core, EASY!Lock manual screw fitting on both sides, and ANTI!Twist. Approved for max. 400 bar pressure.	☐
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	30	6.388-083.0	10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 × 1.5, with kink protection.	☐
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × EASY!Lock	31	6.110-023.0	High-pressure hose with double steel core, ANTI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, approved for max. 400 bar pressure.	☐
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	32	6.391-354.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	☐
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock	33	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	☐
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × M22 × 1.5	34	6.389-709.0	With rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × EASY!Lock	35	6.110-029.0	The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	☐
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × M22 × 1.5	36	6.390-027.0	with rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × M22 × 1.5	37	6.390-294.0	With rotary coupling, 2 × M 22 × 1.5	☐
Food industry version with unions on both sides				
High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock	38	6.110-051.0	High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With EASY!Lock hand screw connection at both ends.	☐
High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × EASY!Lock	39	6.110-052.0	Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections.	☐
High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × M22 × 1.5	40	6.389-479.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 × 1.5 with anti-kink sleeve.	☐
High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × M22 × 1.5	41	6.389-581.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 × 1.5, with kink protection. NW 8/155°C/250 bar.	☐
Longlife food industry version with unions on both sides				
High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock	42	6.110-053.0	With blue, non-marking and animal fat-resistant outer covering: High-pressure hose (ID 8), 10 m long, with ANTI!Twist and EASY!Lock hand screw connection at both ends.	☐

☐ Available accessories.

KÄRCHER

EQUIPMENT FOR ROTARY CLEANER HEAD M63E
6.751-061.0


43


44


31, 33, 35, 46


32, 47


48, 55–56


49


50–51, 54


52–53

		Order no.	Description	
HIGH-PRESSURE HOSES				
Longlife food industry version with unions on both sides				
High-pressure hose food grade Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock	43	6.110-054.0	High-pressure hose with double steel reinforcement and blue, non-marking and animal fat-resistant outer covering. 20 m long with EASY!Lock hand screw connections.	☐
High-pressure hose food grade, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	44	6.391-864.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 × M 22 × 1,5	☐
High-pressure hose food grade, 20 m, ID 8, 400 bar, 2 × M22 × 1.5	45	6.391-887.0		☐
Special hoses				
High-pressure hose Ex, 10 m, ID 8, 400 bar, 2 × EASY!Lock	46	6.110-064.0	Electrically conductive, 10 m long high-pressure hose for use in hazardous areas. 10 m long high-pressure hose with EASY!Lock hand screw connections at both ends.	☐
High-pressure hose electrically conductive, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	47	6.391-741.0	Electrically conductive longlife high-pressure hose for use in hazardous areas with risks of explosions. Delivered with factory certification on conductivity.	☐
Classic				
High-pressure hose Classic, 10 m, ID 10, 250 bar × , EASY!Lock	48	4.119-004.0	High pressure hose with convenient EASY!Lock manual fitting from the Classic series by Kärcher. Also suitable for hot water high-pressure cleaners.	☐
High-pressure hose Classic, 10 m, ID 8, 315 bar × , EASY!Lock	49	4.119-005.0		☐
Hose TR DN8 31,5MPa 20m with package, 20 m, ID 8, 315 bar × , EASY!Lock	50	4.119-006.0		☐
Hose TR DN8 31,5MPa 30m with package, 30 m, ID 8, 315 bar × , EASY!Lock	51	4.119-007.0		☐
Hose TR DN6 25MPa 10m with package, 10 m, ID 6, 250 bar × , EASY!Lock	52	4.119-012.0		☐
Hose assembly with package TR DN6 25MPa, 15 m, ID 6, 250 bar × , EASY!Lock	53	4.119-016.0		☐
Hose assembly with package TR DN8 max31,, 15 m, ID 8, 315 bar × , EASY!Lock	54	4.119-017.0		☐
Hose assembly with package TR DN10 25MPa, 20 m, ID 10, 250 bar × , EASY!Lock	55	4.119-019.0		☐
Hose assembly with package TR DN10 25MPa, 40 m, ID 10, 250 bar × , EASY!Lock	56	4.119-020.0		☐

☐ Available accessories.

KÄRCHER

EQUIPMENT FOR ROTARY CLEANER HEAD M63E
6.751-061.0


57–58


59–60


61


62


63


64, 66


65

		Order no.	Description	
HIGH-PRESSURE HOSES				
Classic				
Hose with transport packaging, 10 m, ID 8, 315 bar × , M22 × 1.5	57	4.760-834.0	High-pressure hose with M22 screw connections from the Classic series from Kärcher. Also suitable for hot water high-pressure cleaners.	☐
Hose M DN8 31,5MPa 20m with package, 20 m, ID 8, 315 bar × , M22 × 1.5	58	4.760-857.0		☐
Hose assembly with package M22 DN10 25MP, 20 m, ID 10, 250 bar × , M22 × 1.5	59	4.760-892.0		☐
Hose assembly with package M22 DN10 25MP, 40 m, ID 10, 250 bar × , M22 × 1.5	60	4.760-893.0		☐
COUPLING PARTS				
Adapter				
Adapter male thread G3/8"-M22x1,5	61	6.651-646.0	Brass adapter 3/8" external thread to M 22 × 1.5 external thread for max. 400 bar, max. 150 °C.	☐
Adapter EASY!Lock				
Adapter 2 M22IG-TR22AG	62	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	☐
STATIONARY HIGH-PRESSURE CLEANING SYSTEMS				
Double connecting	63	5.402-001.0		☐
High-pressure ball valve	64	6.412-066.0		☐
	65	6.412-491.0		☐
STATIONARY HIGH-PRESSURE CLEANERS				
	66	6.412-067.0		☐

☐ Available accessories.