BRUSH SOFT

For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.



Order no.	6.960-135.0

Technical data		
EAN code		4054278824369
Water feed temperature	°C	max. 40
Connecting Thread		M 18
Colour		blue
Weight incl. packaging	kg	1.2



Easy-to-understand colour coding

- The colour coding facilitates the selection of the appropriate brush.

Versatile fields of application

- Integrated high-pressure nozzle for using the brush with a high-pressure cleaner.
- Incl. 2 nozzles and 1 connection piece for use with pure water.
- With 4 nozzle connections for optimal water application.

COMPATIBLE MACHINES

- Cold Water Pressure Washer HD 4/11 C Bp
- Cold Water Pressure Washer HD 5/11 P
- Cold Water Pressure Washer HD 5/12 CX Plus
- Cold Water Pressure Washer HD 6/11-4 M Plus 110v
- HD 10/15-4 Cage Food
- HD 10/21-4 S Plus
- HD 10/25-4 S
- HD 10/25-4 S Classic
- HD 20/15-4 Cage Plus
- HD 4/9 P 110V
- HD 5/12 C Plus
- HD 6/13 C Plus
- HD 6/13 CX Plus
- HD 7/12-4 M Plus
- HD 7/15 G
- HD 8/23 G Classic
- HD 9/20-4 SXA Plus
- HD 9/23 De
- HD 9/23 G
- HD 9/25 G Classic
- HDS 10/21-4 Classic
- HDS 10/21-4 M
- HDS 10/21-4 MXA
- HDS 1000 BE
- HDS 1000 DE
- HDS 13/20-4 S
- HDS 5/11 U
- HDS 5/11 UX
- HDS 6/10 C
- HDS 6/12 C
- HDS 7/10-4M
- HDS 7/16 C
- HDS 8/20 De
- HDS 8/20 G
- HDS 9/20-4 Classic
- HDS 9/20-4 M
- HDS-E 8/16-4 M 12 kW
- HDS-E 8/16-4 M 24 kW
- HDS-E 8/16-4 M 36 kW
- Telescopic lance TL 10 C
- Telescopic lance TL 10 H
- Telescopic lance TL 14 C
- Telescopic lance TL 7 F
- Telescopic lance TL 7 H

Brush soft, 6.960-135.0, 2026-11-06

EQUIPMENT FOR BRUSH SOFT
6.960-135.0







		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING				
Wasserenthärtung				
WS 50	1	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	☐
WS 100	2	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	☐
WS Regenerator	3	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	☐
Hoses				
Water hose 25 m	4	6.392-578.0	Water hose (25 m) for water connection to brushes mounted on telescopic lances for window, façade and solar power installation cleaning.	☐
Water hose 50 m	5	6.392-579.0	50-metre transparent water hose as supply line for the brushes mounted on telescopic lances for window, façade and solar power installation cleaning.	☐
Attachment kits and adapters				
Angle joint	6	4.802-048.0	Up to 180° variable angle joint for connecting telescopic lances and brushes when cleaning facades, windows or solar panels.	☐

☐ Available accessories.