ADAPTATEUR ANTIVRILLE

L'adaptateur antivrille permet de desserrer les boucles du flexible haute pression pour travailler sans risque de torsion. Pour tous les flexibles haute pression avec raccord pratique Quick Connect côté pistolet.



Référence	2.644-257.0

Caractéristiques techniques		
Code EAN		4054278825779
Couleur		Noir
Poids	kg	0,1
Poids emballage inclus	kg	0,1
Dimensions (L × l × h)	mm	137 × 26 × 26



Raccord rapide Quick connect

- Pour les flexibles haute pression avec raccord pratique Quick Connect côté pistolet.

Système Anti-twist

- Le fait de tourner l'adaptateur permet de desserrer les boucles du flexible haute pression.

Fait à partir de laiton

- Fonction de rotation fiable grâce à l'utilisation de laiton.

APPAREILS COMPATIBLES

- Flexible haute pression H 9 Q Quick Connect
- H 10 Q flexible haute pression avec Quick Connect et pour appareils à tambour-enrouleur
- K 4 Comfort Premium
- K 4 Power Control Go!Further
- K 4 Premium Power Control Flex
- K 4 Silent Home
- K 4 WCM
- K 5 Comfort Premium Connect Home
- K 5 Power Control Home & Pipe
- K 5 Premium Smart Control Flex
- K 5 WCM
- K 5 WCM Home
- K 7 Comfort Premium
- K 7 Comfort Premium Connect Home
- K 7 WCM
- K 7 WCM FJ Home BB
- K 5 Comfort Premium
- Set de flexible haute pression HK 12
- Set de flexible haute pression HK 4
- Set de flexible haute pression HK 7,5

Adaptateur antivrille, 2.644-257.0, 2026-10-30