TUYAU PRIMOFLEX® 3/4" – 50 M

Tuyau d'arrosage de qualité supérieure PrimoFlex® (3/4"). Longueur : 50 m. Avec armature tressée résistante à la pression. Sans risque pour la santé. Pression d'éclatement : 24 bar. Plage de températures d'utilisation étendue de 0 à +40 °C.



Référence	2.645-143.0

Caractéristiques techniques		
Code EAN		4039784447639
Diamètre		3/4"
Longueur de flexible	m	50
Couleur		Jaune
Poids	kg	10,5
Poids emballage inclus	kg	10,5
Dimensions (L × l × h)	mm	380 × 380 × 285

Garantie de 12 ans

- Longue durée de vie

3 couches

- Résistant aux nœuds

Pression de cassure 24 bar

- Robustesse garantie

APPAREILS COMPATIBLES

- G 7.180
- K 2 Battery
- K 2 Classic
- K 2 Universal Edition
- K 3 Classic
- K 3 Home
- K 4 Classic
- K 4 Power Control Go!Further
- K 4 Premium Power Control Flex
- K 4 Silent Home
- K 4 WCM
- K 5 Power Control Home & Pipe
- K 5 Premium Smart Control Flex
- K 5 WCM
- K 5 WCM Home
- K 7 WCM
- K 7 WCM FJ Home BB
- K Silent eco!Booster
- KHB 4-18 Plus
- KHB 4-18 Plus Battery Set
- K 2 Premium
- K 2 Start
- K 2 Premium Power Control
- K 3 Power Control
- OC 7-18 Handheld
- OC 7-18 Handheld Battery Set