TUYAU FLEXIBLE PRIMOFLEX 1/2"-25M

Le tuyau d'arrosage souple PrimoFlex® (1/2") est un tuyau d'eau à armature résistante à la pression de 25 m, conçu pour une grande plage de températures et sans danger pour la santé. Pression d'éclatement : 24 bar.



Référence	2.645-297.0

Caractéristiques techniques		
Code EAN		4054278190815
Diamètre		1/2"
Longueur de flexible	m	25
Couleur		Jaune
Poids	kg	2,8
Poids emballage inclus	kg	2,8
Dimensions (L × l × h)	mm	289 × 289 × 142



Garantie de 12 ans

- Longévité

3 couches

- Résistant aux nœuds

Pression d'éclatement 22 bar

- Robustesse garantie

APPAREILS COMPATIBLES

- G 7.180
- K 2 Battery
- K 2 Classic
- K 2 Universal Edition
- K 3 Classic
- K 3 Home
- K 4 Classic
- K 4 Power Control Go!Further
- K 4 Premium Power Control Flex
- K 4 Silent Home
- K 4 WCM
- K 5 Power Control Home & Pipe
- K 5 Premium Smart Control Flex
- K 5 WCM
- K 5 WCM Home
- K 7 WCM
- K 7 WCM FJ Home BB
- K Silent eco!Booster
- KHB 4-18 Plus
- KHB 4-18 Plus Battery Set
- K 2 Premium
- K 2 Start
- K 2 Premium Power Control
- K 3 Power Control
- OC 7-18 Handheld
- OC 7-18 Handheld Battery Set
- PCL 3-18
- PCL 4
- PCL 6